Binnenveld 17
5462 GK Veghel, Nederland
+31(0)413 355746
info@equitrend.nl

MaXuSS Standard



Eigenschappen

The beautifully finished body made of two colours of heat-resistant plastic consists of 3 parts. The solarium follows the horse's lines so that each muscle group is correctly lit by the IR lamps. The front and rear parts can move separately from each other so you can always make the right adjustment for your horse.

The solarium is finished with rounded edges, eliminating the risk of injury to your horse. The lamps are placed higher than the lower surfaces of the solarium, minimising the risk of contact with the hot IR lamps. By using a heat-resistant plastic, placing the lamps in aluminium holders and reusing the residual heat, a very high efficiency can be achieved.

Stylish design
Lightweight design
Flexible shape setting
Higher heat output
Impact-resistant plastic
Splashproof
CE marking

Specificaties

Technical specifications	MaXuSS 230	MaXuSS 400
Lamps		
100-watt IR	10	
150 W IR	12	9
175 Watt IR		
250 Watt IR	2	15
Total IR power in Watts	3300	5100
Fan		
Number	6	9
m3/h	540	810
Automatic at approx. 30 C	Standard	Standard
Connected load		
Connection voltage	1-phase + N + PE 230V 50Hz	3-phase + N + PE 400V 50Hz
Fuse with ... Ampere	16 A	3*10 A
Power consumption Watt	3500	5400
Material and size		

Modules	Heat-resistant plastic	Heat-resistant plastic
Top colour	Dark green	Dark green
Bottom colour	Silver grey	Silver grey
Lamp fixture	Aluminium	Aluminium
Porcelain fitting	Standard	Standard
Heat-resistant wiring 180	Standard	Standard
Suspension	Steel	Steel
Dimensions LxWxH	240 x130 x 80cm	240 x130 x 80cm
Weight	40 kg	40 kg
Guidelines		
Approvals	CE	CE
IP value	IP44	IP44
Shape manually adjustable	Optional	Optional
Shape automatically adjustable	Optional	Optional
Suspension set	Standard	Standard
Cable with plug	Standard	Standard
Recessed fluorescent lighting	Not possible	Optional
Electric lift installation	Optional	Optional
Control box	Optional	Standard

Van stal tot rijbaan, betrouwbare oplossingen voor elke paardenhouder

Wijzigingen voorbehouden